



SPECIFICATION GUIDELINE FOR SRD Series Swing Racks

GL24SRD – 24.00”H x 20.75”W x 24.00”D – 12 RMU

GL36SRD – 36.25”H x 20.75”W x 24.00”D – 19 RMU

GL48SRD – 48.50”H x 20.75”W x 24.00”D – 26 RMU

General

The Wall Mount Swing Racks Deep (SRD) must be UL listed to UL60950-1 (Standard for Information Technology and Communications Equipment, Cabinet, Enclosure and Rack Systems.) Rack shall be 19” EIA 310-D compliant.

The Wall Mount Swing Rack shall be constructed out #12 Gauge cold rolled steel (CRS). Manufacturer must be ISO 9001:2008 registered.

Common features:

- The Swing Racks will ship unassembled.
- The Swing Racks shall have 22.00” of usable depth
- Rack mounting shall be tapped #12-24 on the front face.
- A package of #12-24 hardware shall be included.
- Weight capacity shall be 100 lbs.
- Multiple mounting provision for cable management cinch strap or wire ties.
- The rack mount section will be able to swing a full 180 degrees.
- Release swing rack via Allen wrench/Hex key
- Wall mounting shall be done on 16” on center using keyway holes.
- Swing Racks shall be painted using durable black powder coat paint.