



**SPECIFICATIONS:**

**DIMENSIONS :** 84"H x 24"W @ 19EIA / 28"W@ 23EIA x 30" D: SHIPS FLAT UNASSEMBLED  
**RACK SPACES :** 45 RMU w/ RMU INDICATORS, 19" EIA / 23"EIA : 310-E COMPLIANT  
**CERTIFICATIONS :** UL 2416, RoHS II  
**RAILS RATED AT :** 2500 lbs.  
**COLOR :** DURABLE TEXTURED POWDER COATING  
**BOLT TOGETHER CONSTRUCTION :**  
 VERTICAL CHANNEL RAILS , #12 GA. C.R.S.  
 TOP HORIZONTAL MEMBER, #12 GA. C.R.S.  
 BOTTOM HORIZONTAL FEET, #12 GA. C.R.S.  
 TOP WATERFALL HORIZONTAL SUPPORT, #14 GA. C.R.S.  
 (16) 3/8-16 x 3/4"L BOLTS AND NUTS  
**HARDWARE :** PACKAGE OF QTY-50; #12-24 SCREWS, INCLUDED.  
 (2) PACKAGES OF QTY-10; CM-26 3.5" x 5" PLASTIC CABLE RINGS

|                      |   |   |   |  |
|----------------------|---|---|---|--|
| EST. WEIGHT :<br>N/A | INTERPRET DRAWING PER ASME Y14.5M-1994<br>DIMENSIONAL LIMITS APPLY<br>AFTER APPLICATION OF FINISH<br>DRAWING NOT TO SCALE<br>TOLERANCE UNLESS OTHERWISE NOTED:<br>ANGULAR +/- 1'<br>.XXXX +/- .010<br>.XXX +/- .015<br>.XX +/- .030<br>.X FOR REF. ONLY | <b>NOTICE:</b><br>Use of this document is subject to a confidentiality and nondisclosure agreement with Great Lakes Case & Cabinet Co., Inc. (GLCC) and may not be reproduced, disclosed or utilized in whole or in part without prior written authorization from GLCC. | PART NUMBER:<br>CMRX-45U30-X-SQM6                   | TITLE<br><b>45RU, 84"H x 30"D CABLE MANAGEMENT X RACK, VENDOR LEVEL ASSEMBLY</b> |
|                      | THIRD ANGLE PROJECTION  |   | MATERIAL TYPE:<br>MATERIAL GAUGE:<br>FINISH: POWDER | DRAWN: CND<br>DATE: 3/4/2020<br>CHECKED & APP. DATE:                             |
|                      |   |   | DWG NO:   | REV:   |
|                      |   |   | SHEET: 1 OF 1                                       |  |