



SPECIFICATIONS:

- DIMENSIONS :** 96"H x 24"W @ 19EIA / 28"W@ 23EIA x 36" D: SHIPS FLAT UNASSEMBLED
- RACK SPACES :** 52 RMU w/ RMU INDICATORS, 19" EIA / 23"EIA : 310-E COMPLIANT
- CERTIFICATIONS :** UL 2416, RoHS II
- RAILS RATED AT :** 2500 lbs.
- COLOR :** DURABLE TEXTURED POWDER COATING
- BOLT TOGETHER CONSTRUCTION :**
 - VERTICAL CHANNEL RAILS , #12 GA. C.R.S.
 - TOP HORIZONTAL MEMBER, #12 GA. C.R.S.
 - BOTTOM HORIZONTAL FEET, #12 GA. C.R.S.
 - TOP WATERFALL HORIZONTAL SUPPORT, #14 GA. C.R.S.
 - (16) 3/8-16 x 3/4"L BOLTS AND NUTS
- HARDWARE :** PACKAGE OF QTY-50; #12-24 SCREWS, INCLUDED.
- (2) PACKAGES OF QTY-10; CM-26 3.5" x 5" PLASTIC CABLE RINGS

| | | | | | | |
|----------------------|---------------------------|--|--|---|---|--|
| EST. WEIGHT : N/A | THIRD ANGLE PROJECTION | INTERPRET DRAWING PER ASME Y14.5M-1994 DIMENSIONAL LIMITS APPLY AFTER APPLICATION OF FINISH DRAWING NOT TO SCALE TOLERANCE UNLESS OTHERWISE NOTED: ANGULAR +/- .1" .XXXX +/- .010 .XXX +/- .015 .XX +/- .030 .X FOR REF. ONLY | | NOTICE: Use of this document is subject to a confidentiality and nondisclosure agreement with Great Lakes Case & Cabinet Co., Inc. (GLCC) and may not be reproduced, disclosed or utilized in whole or in part without prior written authorization from GLCC. | PART NUMBER: CMRX-52U36-X-SQM6 | TITLE 52RU, 96.25"H x 36"D CABLE MANAGEMENT X RACK, VENDOR LEVEL ASSEMBLY |
| | | UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES | | | MATERIAL TYPE: MATERIAL GAUGE: FINISH: POWDER | |
| DWG NO: | | DATE: 3/4/2020 | | REV: | | SHEET: 1 OF 1 |