GL7203 PDU

BASIC RACK PDU SPECIFICATION		
Over Current Protection	20A magnetic breakers on 30A models	
Power Whip	20A: 12AWG 3 or 5 wire & 30A: 10AWG 3 or 5 wire	
Operating Temperature	Full nameplate continuous operation: 0-50°C (32-122°F)	
Rack PDU Type	Vertical rack-mount	
Toolless Mounting	61.2" (12.25 spacing standard); 59.05" mounting option available on rack PDU	
USA Assembly	Yes, with local and off-shore sourced components	
Product Warranty	3 year from date of shipment, repair or replace	
Certification/ Agency Approvals	TUV Certified to UL/CSA 60950-1 with NOM Addendum for Mexico, FCC Part 15 Class A Conformance, RoHS Compliant	
Operating Environment	0-50°C (32-122°F), 5-95% Relative Humidity, 0-10,000 ft. (0-3000 meters) Elevation	
Storage Environment	-25-65°C (32-122°F), 5-95% Relative Humidity, 0-10,000 ft. (0-3000 meters) Elevation	
Chassis Dimensions	72"L x 2.18"W x 2.0"D	
Package Dimensions	84"L x 22"W x 5"D (4-Pack); 84"L x 11"W x 5"D (2-Pack); 84"L x 7"W x 5"D (1-Pack)	
Rack PDU Weight	15 lbs. (Actual weight varies slightly based on configuration)	
Packaged Weight	17 lbs. (1 unit - actual weight varies slightly based on configuration)	

POWERLOK CONFIGURATION: GL7203		
Power	30A, 120/208V, 3PH, 8.6 kW	
Unit Length	72"	
Plug Type	NEMA L21-30P	
Whip Length	10'	
Receptacles	36-C13 & 6-C19	
120V Tech Power (5-15R Outlet)	One Outlet	
Cordlok	None	
Monitoring	None	
Color	Carbon	



